

EM-10000 Remote Air Monitor

The Particles Plus EM-10000 is designed for outdoor particulate and gas monitoring. These robust monitors provide reliable, accurate measurement of airborne contamination allowing for the detection of environmental and public health concerns. The first real time monitor to provide 6 accurate particulate size channels.



Realtime Data

6 particle size channels recorded by the EM-10000 Monitor are stored in an internal non-volatile memory at user-defined data sampling rates (1 second to -99 hours). The high time-resolution of the Model EM-10000 measurements provides a near-instantaneous look at changing airborne particulate concentrations, leading to a well-defined model of local point source influences that may disproportionately affect air quality.

Internet-Enabled

Particles Plus systems are configured to allow users to push real-time data to the cloud where sensor outputs can be visualized by authorized stakeholders.

Fully Integrated Low-Cost Air Quality Sensor System


Integration of additional sensors for measurement of environmental and meteorological parameters including relative humidity, temperature, barometric pressure, (optional) carbon dioxide (CO₂), and total volatile organic compounds (TVOC) offers a more complete view of air quality.

Applications

- Airborne Pollution and Environmental Research
- Perimeter or Fence-line Monitoring for Construction, Remediation or Waste Sites
- Mine and Quarry Fence-line Monitoring for dust control operations
- City Wide or Community Air Pollution Monitoring
- Roadside Emissions Monitoring
- Medical Facilities Property Monitoring
- Power Line Wild-Fire Monitoring
- Environmental Disasters
- Monitor for 24 hours a day, 7 days a week, 365 days a year

Features and Benefits

- Concurrent measurement of multiple, user selectable PM sizes from 0.3µm to 10 µm, including TPM of particles up to 25 µm
- Closed-loop humidity control for incoming airstream
- Closed-loop condensation control within the enclosure
- Aerosol Concentration Range of 0.01 to 20,000 µg/m³
- ULTRAGUARD® Fiberglass reinforced polyester NEMA 4 rated outdoor tamper-proof enclosure with internal thermal control
- Optional pole or tripod mount options
- Optional Cloud based data management software subscription available for remote monitoring



Specifications

Model	EM-10000
Size Range	0.3 to 25 μm
Size Channels	Factory calibrated at 0.3, 0.5, 1.0, 2.5, 5.0, 10.0 μm variable binning
Flow Rate / Accuracy	0.1 CFM (2.83 LPM) / +/- 3%
Aerosol Concentration Range	0.01 to 20,000 $\mu\text{g}/\text{m}^3$
Light Source	Long life laser diode
Resolution	.00000003 mg/m^3
Zero Stability	No appreciable drift
Count Modes	Real-Time Meter and graph, cumulative/differential count/ m^3 and count/ ft^3 , and mass concentration (PM)
Log Interval	Minimum 1 second with no hold time, maximum 99 hours
Calibration	NIST traceable
Display	4.3" (10.9 cm) WQVGA (480x272) color touch screen
Internal Vacuum Pump	Internal pump with automatic flow control
Number of Channels	6
Custom Size Channels	Calibration for custom size channels available
Communication Modes	Ethernet, USB. (Optional) Wireless 802.11 b/g, RS485 or RS232.
Environmental Sensor	Temperature and relative humidity probe: -4° to 122°F (-20° to 50°C) $\pm 1^{\circ}\text{F}$ (0.5°C), 0 -100% $\pm 2\%\text{RH}$
Optional Sensors	NDIR CO_2 (0-5000 ppm, resolution 1 ppm, accuracy $\pm 1\%$ FS, Response rate 20 seconds) TVOC PID, 0-50 ppm / min. detection level 5 ppb, accuracy $\pm 1.5\%$, Response rate <3 seconds
Alarm	Alarms for all particle values, environmental sensors, flow and sensor failure
Instrument Calibration	Particle sensor recommended once per year
User Calibration	Field Calibration of Temperature, Humidity, CO_2 and TVOC possible with included utility software
External Surface	ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and Cover
Dimensions (L x W x H)	12.85" x 7.41" x 25.54" (32.7 cm x 18.9 cm x 64.9 cm) includes barb fittings
Weight	12.5 lbs. (5.66 kg)
Accessories	Quick start guide, operating manual on USB flash drive, mounting feet
Optional Accessories	Printed manual, data cable, pole mounting hardware kit
Data Storage	Internal 45,000 sample records (rotating buffer) including particle count data and environmental data
Sample Time	1 second to 99 hours
Power	110 to 240 VAC 50/60 Hz universal in-line power supply
Operating Conditions	-4° to 122°F (-20° to 50°C) / 20% to 95% non-condensing
Warranty	1 year limited warranty. Extended warranties available.

PAT. <https://particlepatents.com/> Additional Patents Pending.

Particles Plus, Inc. reserves the right to change specifications without notice.
Contact hello@particlesplus.com or your local distributor for more details.
Particles Plus and the Particles Plus logo are trademarks of Particles Plus, Inc.
©2020 Particles Plus, Inc. All rights reserved.

REV 20200601-EM10000



31 Tosca Drive
Stoughton, MA 02072 U.S.A.
+1-781-341-6898
www.particlesplus.com